



Fine work in a damp environment

>>Use (*)

This water-repellent treated leather glove is particularly suitable for all kinds of light handling jobs in wet conditions. Carrying raw materials, working with tools (hoes, shovels, drills, sanders ...), maintenance of green spaces, etc. For masons, carpenters, gardeners, farmers, trade logistics, transportation, etc.

>> Technical features

- ✓ All soft cow grain leather.
- ✓ Special water repellent leather.
- ✓ Shirred elastic back.
- ✓ Gunn cut pattern.
- ✓ Wing thumb.
- ✓ **Color:** beige.
- ✓ **Sizes:** 8, 9, 10, 11.
- ✓ **Packing:** Carton of 100 pairs.
Bundle of 10 pairs.



Learn more : www.singer.fr



>> Advantages

- ✓ Quality of the leather, selected with care for its high softness and its dexterity.
- ✓ Water resistant treatment for duties even in humid environment while you benefit from the traditional comfort and advantages of the natural leather.
- ✓ Very comfortable wear. Very good touch. A high quality glove.
- ✓ **ISO 9001** certified manufacturing.

>> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.


It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by **SGS**. Notified body n°0120 / 0598.

Download the EC declaration of conformity on: <http://docs.singer.fr>



| EN 388: 2016. Protective gloves against mechanical risks | | | | | | | |
|--|---------|---------|---------|----------|---------|----------|----------|
| Mechanical data. Information about levels. | Level 1 | Level 2 | Level 3 | Niveau 4 | Level 5 | Levels ▼ | |
| Abrasion resistance (number of cycles) | 100 | 500 | 2000 | 8000 | - | 2 | |
| Blade cut resistance (index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 | 1 | |
| Tear resistance (in Newtons) | 10 | 25 | 50 | 75 | - | 2 | |
| Perforation resistance (in Newtons) | 20 | 60 | 100 | 150 | - | 1 | |
| Cut resistance (as per EN ISO13997) (TDM test) | Level A | Level B | Level C | Level D | Level E | Level F | Level |
| | 2 | 5 | 10 | 15 | 22 | 30 | X |



«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS_2019_03_14. Copyright: Singer, Fotolia