



>> Use (*)

Thanks to its technical characteristics this glove is particularly suitable for all the main works requiring dexterity and protection against mechanical hazards: automotive assembly, handling of abrasives; tiles, ceramics, plates, sharp objects.

>> Technical features

- ✓ **Construction:** seamless knitted glove.
- ✓ **Fibres:** glass fibres mixed with other synthetic fibres.
- ✓ **Colour:** grey coating / black liner.
- ✓ **Gauge:** 10.
- ✓ **Coating:** bi-polimer (Nitrile/PU).
- ✓ **Sizes:** 7 to 11.
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.



Learn more: www.singer.fr



>> Advantages

- ✓ **Seamless construction:** improves user comfort (will avoid rough points and consequently the risk of reddening or irritation of the skin).
- ✓ **Protective coating:** bi-polimer. For a good protection, palm of this glove is coated with two bi-polimer material. This coating will allow to have new performance: high resistance against oil and grease thanks to the nitrile, and flexibility, resistance to the external aggression as ozone; oils thanks to the nitrile.

>> Conformity


This glove has been tested as per:

- **EN 420 : 2003 +A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type-examination certification issued by **SATRA (Irland)**. Notified body **n°2777**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	EN 388 : 2016  4 X 3 1 B
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	X	
Tear resistance (in Newtons)	10	25	50	75	-	3	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	B

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

