

Stretch nylon



>> Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all light handling, fine works in dry conditions...
 Also suitable as an inner glove and also allows when necessary to protect the product handled from fingerprints, dirt...
 Packing, automotive assembly, electronics and delicate assembly, products inspection...

>> Technical features

- ✓ **Construction:** seamless knitted pattern. Elasticated wrist.
- ✓ **Liner:** stretch nylon.
- ✓ **Gauge:** 13.
- ✓ **Coating:** uncoated (ambidextrous).
- ✓ **Color:** white.
- ✓ **Sizes:** M (9), L (10), XL (11).
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.



Learn more: www.singer.fr



>> Advantages

- ✓ **Seamless construction:** improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity and reduces hand fatigue.
- ✓ **Uncoated** for optimum ventilation and improved softness.
- ✓ **Elasticated knitted wrist** for a snug fit.
- ✓ **Ambidextrous:** the seamless construction of this glove and the uncoated palm allows it to be ambidextrous so it can be used either right hand or left hand.
- ✓ **Designed to produce minimal lint and dust:** reduces the risk of product contamination.

>> Conformity

This glove has been tested according to the following European standards :


- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	1	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	4	
Perforation resistance (in Newtons)	20	60	100	150	-	2	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X



«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

