



**Uses (\*)**

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a good protection against mechanical risks including cut (cut level B, as per EN388 European standard).

Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly, engineering works...

**Technical features**

- ✓ **Construction** : seamless knitted liner.  
Elasticated knitted wrist.
- ✓ **Composition** : HDPE fibers with wrapped glass fibers and polyamide. PU coating on palm.
- ✓ **Colour** : grey.
- ✓ **Gauge** : 13.
- ✓ **Sises** : 7 à 11.
- ✓ **Packing** : - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)

**Highlights**

- ✓ This glove provides a good cut resistance, while providing greater dexterity and comfort.
- ✓ It provides good protection against abrasion and tear in dry conditions handling.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ Excellent grip in dry conditions for safe and secure handling.



**Conformity**

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**  
EU type examination certificate (module B) issued by the **CTC**, notified body n°0075.

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels PHD3PU	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>X</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Puncture resistance (in Newtons)	20	60	100	150	-	<b>2</b>	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level PHD3PU
	2	5	10	15	22	30	<b>B</b>

**EN 388 : 2016**

**4 X 4 2 B**

«X means that the glove has not been submitted to the test.

