



### Type of use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut (**cut level C**, as per EN388 European standard). Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly. Handling fibreboards, blocks...

### Technical features

- ✓ **Construction:** Seamless knitter liner. Elasticated knitted wrist. HDPE fibres (High Density Polyethylene).
- ✓ **Colour:** grey/black.
- ✓ **Gauge:** 13.
- ✓ **Coating:** Soft crinkle latex coating on palm. Open back (ventilated).
- ✓ **Sizes:** 9 to 11.
- ✓ **Packing:** - Carton of 100 pairs.  
- Bundle of 10 pairs.

Learn more: [www.singer.fr](http://www.singer.fr)



### Advantages

- ✓ These gloves provide excellent cut resistance while providing greater dexterity and comfort.
- ✓ This product provides good protection against cut and tear in dry conditions handling.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ Excellent grip in dry conditions for safe and secure handling.



### Conformity

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.

EN 388 : 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels PHD5LAT	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>3</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>X</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Puncture resistance (in Newtons)	20	60	100	150	-	<b>2</b>	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level PHD5LAT
	2	5	10	15	22	30	<b>C</b>

**EN 388 : 2016**

**3 X 4 2 C**

«X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

