



**Type of uses (\*)**

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut (cut level C, as per EN388 European standard).

Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly. Handling fibreboards, blocks...

**Technical features**

- ✓ **Construction:** Seamless knitter liner. HDPE fibres (High Density Polyethylene). Open back (ventilated). Elasticated knitted wrist.
- ✓ **Colour:** gris/black.
- ✓ **Gauge:** 13.
- ✓ **Coating:** Nitrile foam coating on palm.
- ✓ **Sizes:** 8, 9, 10, 11.
- ✓ **Packing:** - carton of 100 pairs.  
- bundle of 10 pairs.



More information: [www.singer.fr](http://www.singer.fr)

**Advantages**

- These gloves provide excellent cut resistance while providing greater dexterity and comfort.
- This product provides good protection against cut and tear in dry conditions handling.
- Elasticated knitted wrist for a snug fit.
- The seamless liner provides exceptional comfort and reduces hand fatigue.
- The back of the glove uncoated allowing the hand to breathe.
- Soft, foam nitrile coating on palm not only enhances protection but it also provides good wet grip by channeling away excess fluid from the surface.



**Conformity**

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.

EN 388 : 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels PHD5NIF	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>X</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Puncture resistance (in Newtons)	20	60	100	150	-	<b>2</b>	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level PHD5NIF
	2	5	10	15	22	30	<b>C</b>

**EN 388 : 2016**

**4 X 4 2 C**

«X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

