


Full grain leather



>> Use (\*)

Thanks to its technical characteristics this product is ideal for your work in the industrial sector, production and repair workshop etc.

Maintenance worker, mechanic, fitter, assembly line driver, coachbuilder ...

>> Technical features

- ✓ Low cut safety shoes.
- ✓ Full grain leather.
- ✓ Top of upper with lining.
- ✓ Tongue gusset.
- ✓ Pierce resistant midsole and safety toe-cap.
- ✓ Fastening with laces and eyelets.
- ✓ Colour: black.
- ✓ Sizes: 39 to 47.
- ✓ Packaging: - Carton of 10 pairs.  
- Each pair individually packed in a box.



670g<sup>(1)</sup>



Learn more: [www.singer.fr](http://www.singer.fr)

<sup>(1)</sup> Approximative weight of a shoe (smaller size)

>> Advantages

- ✓ Convenient full piece and removable footbed. Dual-density PU outsole.
- ✓ Light weight and comfortable safety shoe. Quality of raw material and workmanship.
- ✓ Soft textile pierce resistant midsole.
- ✓ Composite toe cap.
- ✓ Dual lace system. Riveted at stress points for greater strength.

>> Compliance



This safety shoe has been tested according to the following European Standard (Category II).

- **EN ISO 20345: 2012.** Personal protective equipment - Safety footwear.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE).

EU type examination certificate (module B) issued by **CIMAC (Italy)**, notified body n°0465.



Protection	Symbol <b>S3</b>	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol <b>SRC</b>	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your distributor **SINGER® SAFETY**

