




680g<sup>(1)</sup>



>> Use (\*)

Thanks to a careful workmanship and a strict selection of materials, this equipment can be used for indoor or outdoor work activities, for many jobs in the industry, logistics, transport, parks maintenance, crafts or building and public works...

>> Technical features

- ✓ High cut safety shoes.
- ✓ Water repellent leather upper. Metal hooks fastening.
- ✓ Steel 200J toe cap.
- ✓ Tongue with gusset.
- ✓ Antistatic and removable insole made of EVA fabric.
- ✓ Steel puncture resistant midsole.
- ✓ Double-density polyurethane injected sole.
- ✓ Black Colour. Black stitching.
- ✓ Sizes : 39 to 47.
- ✓ Packing : Carton of 10 pairs.

Bundle of 1 pair.



Learn more : [www.singer.fr](http://www.singer.fr)

<sup>(1)</sup> Approximative weight of a shoe (smaller size)

>> Advantages

- ✓ 3 flex zones on the sole for an optimal flexibility
- ✓ Energy absorbing heel.



>> Compliance



This safety shoe has been tested according to the following European Standard (Category II).

- EN ISO 20345: 2012. Personal protective equipment - Safety footwear.

It complies with the European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE).

EU type examination certificate (module B) issued by INTERTEK Italia Spa Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol <b>S3</b>	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol <b>SRC</b>	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your partner **SINGER® SAFETY**

