

ARENDA S2

72002

CE UNI EN ISO 20345:2012 S2 SRC ESD CLASS 3

Low shoe, MICROWASH thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.

COMPLETEL Y METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

SOLE ERGO SAFE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort:

perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm

EN ISO 61340-4-3:2001 for the electrical resistance **ESD class**

3 (electric dissipative footwear)

Size 36-47 Shoe weight Sz 42 gr. 420




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



Ergo Safe is the safety shoe useful for people who have problems with back and joint pains. It is in fact the only ergonomic shoe in the market, studied to give a solution to these needs and in the same time to assure a complete protection. This is possible thanks to the round sole, that allows a uniform discharge of body weight all along the sole of the foot, giving a good feeling to the back, the knees and to the heels. Ergo is also studied to improve walking, by giving a better blood circulation and a saving of energy at the end of the day.

PLUS



MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
SRC		
ANS-SLIPPING SOLE		
SRA ceramic + NaLS	HEEL >= 0,28	0,31
	FLAT >= 0,32	0,35
SRB steel + glycerol	HEEL >= 0,13	0,22
	FLAT >= 0,18	0,22