

# BALTIC S2

KU0201

CE UNI EN ISO 20345:2012 S2 SRC ESD CLASS 3

High shoe, MICROWASH thickness 1,8 ± 2,0 mm.  
Highly perspiring and abrasion resistant fabric lining.

## COMPLETELY METAL FREE SHOE

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 5000, three-materials extracomfort:** perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric dissipative footwear)**

**Size 35-47 Shoe weight Sz 42 gr. 505**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).


## PLUS



### MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
	<b>SRC</b>	
	ANTI-SLIPPING SOLE	
<b>SRA</b> ceramic + NaLS	HEEL >= 0,28	0,46
	FLAT >= 0,32	0,43
<b>SRB</b> steel + glycerol	HEEL >= 0,13	0,30
	FLAT >= 0,18	0,29