

# CAIRO S3 CI HI HRO

HR068D

CE UNI EN ISO 20345:2012 S3 CI HI HRO SRC

High shoe, WRU back leather thickness 1,8-2,0 mm.  
Perspiring and abrasion resistant fabric lining.  
Shoe with refracting fabric insert.  
Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE HARD ROCK ANTISTATIC** bidensity polyurethane and antistatic **RUBBER**.

Sole resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring

**CI** cold insulation of sole complex -17 °C

**HI** heat insulation of sole complex

**HRO** resistance to hot contact of the outsole

**Size 39-47 Shoe weight Sz 42 gr. 585**




## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



Hard Rock Antistatic is a shoe born to face the most extreme working conditions thanks to its rubber outsole. It has been studied to assure the maximum resistance to the most difficult weather conditions (from -30°C to 300°C) and the maximum protection against external cutting bodies (ex. slippers, etc.). Also uppers have been studied to face the most difficult working situations and for this reason the materials comply with the most advanced heat-insulating and water-repellent technologies.

## PLUS

## ANTISLIPPING TEST RESULTS

### ANTISLIPPING TEST RESULTS



**SRC**  
ANTI-SLIPPING SOLE

<b>SRA</b> ceramic + NaLS	<b>HEEL</b> >= 0,28	<b>0,48</b>
	<b>FLAT</b> >= 0,32	<b>0,44</b>
<b>SRB</b> steel + glycerol	<b>HEEL</b> >= 0,13	<b>0,22</b>
	<b>FLAT</b> >= 0,18	<b>0,20</b>