

# HAMBURG S3 CI WR

AC058L

CE UNI EN ISO 20345:2012 S3 CI WR SRC

High shoe, full grain IDROTECH® WRU leather thickness 1,8-2,0 mm, with refracting insert.

Heel area with WRU anti-scratch back leather thickness 1,8-2,0 mm. Soft Windtex® water resistant membrane lining, with very good perspiration and abrasion resistance.

Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring

**CI** cold insulation of sole complex -17°C

**WR** water resistant shoe

Size 36-49 Shoe weight Sz 42 gr. 625



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



## SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

## ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
<b>SRC</b> ANTI-SLIPPING SOLE		
<b>SRA</b> ceramic + NaLS	<b>HEEL</b> >= 0,28	<b>0,39</b>
	<b>FLAT</b> >= 0,32	<b>0,36</b>
<b>SRB</b> steel + glycerol	<b>HEEL</b> >= 0,13	<b>0,26</b>
	<b>FLAT</b> >= 0,18	<b>0,22</b>

## PLUS



### WINDTEX®

Windtex® is an innovative membrane that blocks wind and water, by guaranteeing at the same time a homogeneous transpiration of the foot. The degree of transpiration of Windtex® together with windproof property, allow the maintenance of microclimate of the shoe. This membrane, with technology Aegis®, builds and antimicrobial barrier against unpleasant odors, fungi and other microorganisms.



### IDROTECH®

IDROTECH® is a leather treatment with the aim to optimize the water resistance and the foot perspiration. This particular tanning method, thanks to the used mineral salts, gives an excellent softness and a complete mechanical resistance to oils and hydrocarbons. The IDROTECH® leather is certified according to the norms ISO 4045, ISO 17075 and ISO 5403.