

LUTON 03 FO

C70680C

CE UNI EN ISO 20347:2012 O3 FO SRC ESD

High shoe, MICROWASH thickness 1,8-2,0 mm.
Perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE CITY bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

FO sole resistance to hydrocarbons

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



Size 36-47 Shoe weight Sz 42 gr. 540

SOLE



City is a unique styled shoe, perfect for people who look for a safety shoe to use in a lot of different situations, free time included. Giasco developed for this product a special gel insert in the heel zone, called G-GEL, useful to reduce the impact stress et to release energy during walking. This sole has been studied with a special attention to the design of uppers and sole and to the technology of hidden outsole.

PLUS



MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
SRC ANTI-SLIPPING SOLE		
SRA ceramic + NaLS	HEEL >= 0,28 FLAT >= 0,32	0,52 0,52
SRB steel + glycerol	HEEL >= 0,13 FLAT >= 0,18	0,18 0,20