

OXFORD S3

KU068D

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, back WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoes with refracting fabric insert.

Soft, lined and padded tongue.

The shoe satisfies the requirements of slipping resistance on

inclined roofs according to **UNI 11583:2015**

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4000, removable, anatomic, absorbing, antistatic and perspiring

Size 35-49 **Shoe weight** Sz 42 **gr. 550**



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



LOGISTICS AND LIGHT INDUSTRY



ROOFER

SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
	SRC	ANTI-SLIPPING SOLE	
SRA ceramic + NaLS	HEEL >= 0,28	0,46	
	FLAT >= 0,32	0,43	
SRB steel + glycerol	HEEL >= 0,13	0,30	
	FLAT >= 0,18	0,29	