

# PANAMA S1P

KU083T

CE UNI EN ISO 20345:2012 S1P SRC

Low holed shoe, suede back leather thickness 1,8-2,0 mm.

Highly perspiring and abrasion resistant fabric lining.

Soft, lined and padded tongue.

**COMPLETELY METAL FREE SHOE**

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4000**, removable, anatomic, absorbing, antistatic and perspiring

**Size 35-49 Shoe weight Sz 42 gr. 530**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



COMPONENTS AND AUTOMOTIVE



WOOD METAL CARPENTRY



LOGISTICS AND LIGHT INDUSTRY

## SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

## PLUS

## ANTISLIPPING TEST RESULTS

### ANTISLIPPING TEST RESULTS



**SRC**  
ANTI-SLIPPING SOLE

|                                   |                     |             |
|-----------------------------------|---------------------|-------------|
| <b>SRA</b><br>ceramic +<br>NaLS   | <b>HEEL</b> >= 0,28 | <b>0,46</b> |
|                                   | <b>FLAT</b> >= 0,32 | <b>0,43</b> |
| <b>SRB</b><br>steel +<br>glycerol | <b>HEEL</b> >= 0,13 | <b>0,30</b> |
|                                   | <b>FLAT</b> >= 0,18 | <b>0,29</b> |