

SOLDADOR S3

AC880BSP

CE UNI EN ISO 20345:2012 S3 SRC

High shoe, water-resistant WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

High visibility fabric insert. Lined and padded tongue.

Shoe with dross protective leather cover tongue and side closing Nby click buckle.



TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE antiperforation steel according to EN 12568

SOLE ACTION bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 1000, in high density and open cells latex foam.

Absorbing, antistatic and perspiring

Size 39-47 Shoe weight Sz 42 gr. 635

CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



WOOD METAL CARPENTRY



BUILDING AND HEAVY INDUSTRY



WELDER


SOLE



Action is a shoe studied for external jobs, with soft lines making it very light and comfortable.

PLUS

ANTISLIPPING TEST RESULTS

| ANTISLIPPING TEST RESULTS | | |
|--|------------------------------|--------------|
|  | SRC | |
| ANTI-SLIPPING SOLE | | |
| SRA ceramic + NaLS | HEEL >= 0,28 FLAT >= 0,32 | 0,39 0,36 |
| SRB steel + glycerol | HEEL >= 0,13 FLAT >= 0,18 | 0,26 0,22 |