

STOCKHOLM S3

KU1911

CE UNI EN ISO 20345:2012 S3 SRC ESD

Low shoe, MICROWASH thickness 1,8 - 2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoes satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance

ESD

Size 36-47 Shoe weight Sz 42 gr. 455



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).


PLUS



MICROWASH

MICRO WASH is a Chrome free material finished with perspiring polyurethanes. Very light and perspiring, it is suitable for alimentary et hospital sectors. It is also studied for people wearing the shoes for a lot of hours on wet surfaces. It resists to acids, mostly oleic acid. It is washable with water and neutral soap at 40°.

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
	SRC	ANTI-SLIPPING SOLE	
SRA ceramic + NaLS	HEEL >= 0,28	0,46	
	FLAT >= 0,32	0,43	
SRB steel + glycerol	HEEL >= 0,13	0,30	
	FLAT >= 0,18	0,29	