

VOLARE S3

KU073T

CE UNI EN ISO 20345:2012 S3 SRC ESD CLASS 3

Low shoe, WRU suede back leather thickness 1,8 □ 2,0 mm. Highly perspiring and abrasion resistant fabric lining.
Soft and lined tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric composite non-thermic according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial
The shoe satisfies the requirement according to the norm IEC 61340-4-3:2001 for the electrical resistance **ESD class 3 (electric dissipative footwear)**

Size 35-47 Shoe weight Sz 42 gr. 564



CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS




SOLE



In order to avoid the high number of accidents caused by slipping danger, Giasco realized an excellent anti-slipping product. This sole is called Kube, a young and sporty styled shoe equipped with a special gripping compound and specific cubic dowels with inverted profile in the outsole. With thanks to these special characteristics Kube obtained the maximum certification against slipping: jobs on inclined roofs (UNI 11583:2015).

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS			
	SRC	ANTI-SLIPPING SOLE	
SRA ceramic + NaLS	HEEL >= 0,28	0,46	
	FLAT >= 0,32	0,43	
SRB steel + glycerol	HEEL >= 0,13	0,30	
	FLAT >= 0,18	0,29	