

WELDER S3 CI HRO

4X122D

CE UNI EN ISO 20345:2012 S3 CI HRO SRC

Low shoe, WRU back leather thickness 1,8-2,0 mm, with refracting fabric insert.

Perspiring and abrasion resistant fabric lining.

Leather mask stitched with fireproof wire.

Closing with strap.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE RUBBER 4X4 ANTISTATIC bidensity: polyurethane and antistatic **RUBBER**. Sole resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

CI cold insulation of sole complex -17°C

HRO resistance to hot contact of the outsole

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and antibacterial

Size 39-47 Shoe weight Sz 42 gr. 550




CERTIFICATIONS



TECHNOLOGIES AND MATERIALS



SECTORS



SOLE



4X4 is the PU/Rubber line studied for the working places where extreme temperatures are a danger for shoes resistance and consequently for workers. For this reason the specific compound of the outsole is studied to assure a complete protection from -17°C until 300°C. At the same time the expanded midsole assures the best comfort while walking, thanks to its low density.

PLUS

ANTISLIPPING TEST RESULTS

ANTISLIPPING TEST RESULTS		
SRC ANTI-SLIPPING SOLE		
SRA ceramic + NaLS	HEEL >= 0,28	0,55
	FLAT >= 0,32	0,55
SRB steel + glycerol	HEEL >= 0,13	0,22
	FLAT >= 0,18	0,28