

# WOODCUT S3 - III/L.2

CE EN ISO 20345:2011 S3 WR CI HI HRO

Calf boot, WRU grain leather thickness 2,0-2,2 mm, boot with anti-cut insert made with high resistance textile. Anti-Abrasion rubber insert on the toecap. Tnt lining doubled with perspiring and abrasion resistant TE-POR® membrane.

Soft back leather tongue, perspiring and abrasion resistant. BASIC REQUIREMENTS OF THE FOOTWEAR WITH CUTTING RESISTANCE FROM CHAIN SAW (EN ISO 17249:2013 Level 2: chain speed for the 24 m/s test).

**TOECAP 200J steel** EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE with ANTITORSION internal support, NITRILIC RUBBER** black color, with orange heat resistant insert, antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, antishock and anti-slipping **SRC**

**INSOLE** expanded material removable, anatomic, absorbing, antistatic and perspiring

**CI** cold insulation of sole complex -17°C

**HI** heat insulation of sole complex

**WR** water resistant shoe

**HRO** resistance to hot contact of the outsole

Boot height sole included 23 cm

**Size 39-47 Boot weight Sz 42 gr. 1160**



## CERTIFICATIONS



## TECHNOLOGIES AND MATERIALS



## SECTORS



FARMING AND MINING



BUILDING AND HEAVY INDUSTRY



COLD

PLACES

**SOLE**

**PLUS**